

50 Ohm Radiating Cable, 1/2" - AR012J50

Description	Product Number
Standard Cable	
1/2", Black Polyethylene Jacket	AR012J50
Features & Benefits	
100% Made in the USA (Buy America, Title 49 Compliant)	
UV Rated for Outdoor Use	
No Water Migration 15 Year Warranty	
Indication of Slot Alignment	None
Recommended Hanger Spacing, ft (m)	6 (2)
Minimum Distance to Wall, in (mm)	2 (50.8)
Jacket Color	Black
Physical Dimensions	
Center Diameter, in (mm)	0.188 (4.78)
Diameter Over Dielectric, in (mm)	0.480 (12.19)
Diameter Over Outer Conductor, in (mm)	0.512 (13.00)
Maximum Diameter Over Jacket, in (mm)	0.592 (15.04)
Center Conductor	Copper-Clad Aluminum
Outer Conductor	Dual Slotted Solid Aluminum Tube
Electrical Characteristics	
Maximum Frequency, GHz	11
Peak Power Rating, KW	32
DC Resistance, Ohms/1,000 ft (1,000 m)	
Center	0.46 (1.51)
Outer	0.52 (1.71)
DC Breakdown, kV	3.2
Capacitance, pF/ft (m)	22.3 (73.16)
Inductance, mH/ft (m)	0.056 (0.184)
Jacket Spark, kV RMS	8
VSWR min, (dB)	1.38 (16.0)
VSWR in-band, (dB)	1.30 (17.7)
Impedance, Ohms	50 ± 2
Velocity of Propagation	91%
Stop Bands, MHz	1051 - 1065, 1103 - 1106, 2208 - 2213
Mechanical Characteristics	
Minimum Bend Radius, in (mm) - Single	2 (50.8)
Cable Weight, lb/ft (kg/m)	0.12 (0.18)
Bending Moment, ft lb (N m)	7.5 (10.2)
Tensile Strength, lb (kg)	465 (211)
Flat Plate Crush, lb/in (kg/mm)	62 (1.11)
Recommended Install Temp., °F (°C)	-10° to 170° (-23° to 77°)
Recommended Storage Temp., °F (°C)	-40° to 170° (-40° to 77°)
Recommended Operating Temp., °F (°C)	-40° to 170° (-40° to 77°)
Regulatory Compliance/Certifications	
RoHS 2011/65/EU Compliant	
TL 9000 H-V - All Cables designed and manufactured under this quality management system	



Electrical Performance			
Frequency, MHz	Attenuation		Coupling Loss
	dB/100 ft	dB/100 m	95%, dB
150	0.95	3.12	84 (85)
220	1.18	3.88	84 (85)
450	1.68	5.52	84 (85)
500	1.80	5.90	81 (82)
700	2.24	7.34	87 (88)
800	2.34	7.68	83 (86)
900	2.51	8.22	86 (87)
1000	2.76	9.06	86 (88)
1700	3.59	11.78	88 (89)
1800	3.71	12.16	88 (89)
1900	3.82	12.54	88 (90)
2000	3.98	13.05	89 (90)
2100	4.10	13.43	89 (91)
2200	4.21	13.82	89 (90)
2400	4.39	14.40	86 (89)
2600	4.92	16.14	88 (89)
2700	5.18	16.98	86 (87)

Notes:

- Coupling Loss and Attenuation Values are measured in accordance with the IEC 61196-4 Free Space Test Method
- Coupling Loss values are measured with a radial (below 330 MHz) or orthogonal (above 330 MHz) orientated dipole antenna
- The Coupling Loss values in parentheses are the mean values of all three spatial orientations (radial, parallel and orthogonal) of dipole antenna
- Coupling Loss Tolerance of ± 10 dB at 6 ft (2m), 95%
- Attenuation Tolerance of ± 10% at 68°F
- As is the case with all radiating cables, performance in RF confined areas may differ from values in a free space.

Trilogy AirCell® Cable

Proud to be 100% Made in the USA

